




House Pet - Frog

\$18.00/tile

The Original—a playful, whiskery texture like a wire-haired terrier (think faux mohair) in a spectrum of amazing colors. This product is not recommended for use over radiant heat floors. Style not eligible for cutting service. Made in Holland 82.5% nylon/17.5% polyester Heavy traffic Parquet (quarter-turn) installation This style is not eligible for our Cutting Service

Installation



Parquet (Quarter-Turned) Installation

General Information

| | |
|-------------------------|--|
| Product Number | 211031 |
| Construction | Textured Needle-punch Pile |
| Soil/Stain Protection | No |
| Antimicrobial Treatment | (AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept |
| Fiber Content | 82.5% Nylon/17.5% Polyester |
| Dye Method | 100% Solution Dye |
| Post-Industrial | 36% |
| Post Consumer | 0% |
| Total Recycled Content | 36% |
| Adhesive | FLORdots®; |

Product Specifications

| | |
|--------------------|-----------------------|
| Tufted Yarn Weight | 41 oz/yd ² |
| Machine Gauge | Needle-punch |
| Pile Thickness | .133 in |
| Pile Density | 11,964 |
| Total Thickness | .340 in |
| Size | 19.7 in x 19.7 in |

Performance Specifications

| | |
|------------------|------------------------|
| Radiant Panel | (ASTM E - 648) Class 1 |
| Smoke Density | (ASTM E - 662) |
| Lightfastness | (AATCC16-E) |
| Static | (AATCC - 134) < 3.0 KV |
| Standard Backing | Graphlar Tile |

*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

*To find out more about our recycled content, please visit FLOR's Environmental Efforts.