




Take A Ribbing - Sand

\$12.00/tile

Subtle lines of ribbing provide a soft, pleasant feel underfoot. The beveled edging gives a clean, crisp look. Made in the USA 41-45% recycled face fibers Medium traffic Quarter-turn installation

Installation



Parquet (Quarter-Turned) Installation

General Information

Product Number	211070
Construction	Cut Pile
Soil/Stain Protection	No
Antimicrobial Treatment	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept
Fiber Content	Nylon
Dye Method	100% Solution Dye
Post-Industrial	41-45%
Post Consumer	0%
Total Recycled Content	41-45%
Adhesive	FLORdots®;

Product Specifications

Tufted Yarn Weight	28 oz/yd ² ;
Machine Gauge	1/10 in
Pile Height	.21 in
Pile Thickness	.162 in
Stitches	12/in
Pile Density	6267
Total Thickness	.303 in
Size	19.7 in x 19.7 in

Performance Specifications

Indoor Air Quality	Green Label Plus Certified
Radiant Panel	(ASTM E - 648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC16-E)
Static	(AATCC - 134) < 3.0 KV
Standard Backing	GlasBac Tile

*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

*To find out more about our recycled content, please visit FLOR's Environmental Efforts.