



Working Class - Tan

\$12.00/tile

A dense, flat and slightly coarse weave suitable for your most demanding spaces–yes, even garages. This product is not recommended for use over radiant heat floors. Style not eligible for cutting service.Made in the Holland100% polypropyleneHeavy trafficStraight installationThis style is not eligible for our Cutting Service

Installation



Monolithic (Straight) Installation

General Information

Product Number	211088
Construction	Needlepunch Pile
Soil/Stain Protection	No
Antimicrobial Treatment	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept
Fiber Content	100% Polypropylene
Dye Method	100% Solution Dye
Post-Industrial	0%
Post Consumer	0%
Total Recycled Content	0%
Adhesive	FLORdots™

Product Specifications

Tufted Yarn Weight	25 oz/yd2
Machine Gauge	Needlepunch
Pile Height	.14 in
Pile Thickness	.34 in
Pile Density	6069
Total Thickness	.250 in
Size	19.7 in x 19.7 in

Performance Specifications

Radiant Panel	(ASTM E - 648) Class 2
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC16-E)
Static	(AATCC - 134) < 3.0 KV
Standard Backing	Graphlar
Foot Traffic	Heavy

*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

*To find out more about our recycled content, please visit FLOR's Environmental Efforts.