




# Toy Poodle - Orchid

\$14.00/tile

Curly, loop construction in an abundance of colors&ndash;from lively bights to tamely muted&ndash;provides a soft and nubby surface. The beveled edging provides a crisp, clean look. Made in the USA38-44% recycled face fibersMedium trafficStraight installation

## Installation



Monolithic (Straight) Installation

## General Information

|                         |                                                    |
|-------------------------|----------------------------------------------------|
| Product Number          | 211089                                             |
| Construction            | Textured Loop Pile                                 |
| Soil/Stain Protection   | No                                                 |
| Antimicrobial Treatment | (AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept |
| Fiber Content           | Nylon                                              |
| Dye Method              | 100% Solution Dye                                  |
| Post-Industrial         | 38-44%                                             |
| Post Consumer           | 0%                                                 |
| Total Recycled Content  | 38-44%                                             |
| Adhesive                | FLORdots&trade;                                    |

## Product Specifications

|                    |                   |
|--------------------|-------------------|
| Tufted Yarn Weight | 36 oz/yd2         |
| Machine Gauge      | 1/12 in           |
| Pile Height        | .20 in            |
| Pile Thickness     | .178 in           |
| Stitches           | 10/in             |
| Pile Density       | 7180              |
| Total Thickness    | .326 in           |
| Size               | 19.7 in x 19.7 in |

## Performance Specifications

|                    |                            |
|--------------------|----------------------------|
| Indoor Air Quality | Green Label Plus Certified |
| Radiant Panel      | (ASTM E - 648) Class 1     |
| Smoke Density      | (ASTM E - 662)             |
| Lightfastness      | (AATCC16-E)                |
| Standard Backing   | GlasBac Tile               |

\*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

\*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

\*To find out more about our recycled content, please visit FLOR's Environmental Efforts.