

Drysdale - Shale

\$35.00/tile

Low loop furrows alongside higher, cut and loop ribs in muted tones provides an understated textural variation that offers an elegant and luxurious look. Made in the USA 100% pure British wool face fibers Medium traffic Quarter-turn installation

Installation



Parquet (Quarter-Turned) Installation

General Information

Product Number	241307
Construction	Multi Level Cut & Loop
Soil/Stain Protection	No
Antimicrobial Treatment	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept
Fiber Content	100% British Wool
Dye Method	Blended Undyed & Skein Dyed
Post-Industrial	37%
Post Consumer	0%
Total Recycled Content	37%
Adhesive	FLORdots™

Product Specifications

Tufted Yarn Weight	40 oz/yd ²
Machine Gauge	1/8 in
Pile Height	.25 in
Pile Thickness	.236 in
Stitches	10/in
Pile Density	5644
Total Thickness	.390 in

Performance Specifications

Radiant Panel	(ASTM E - 648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	AATCC 16- E
Standard Backing	GlasBac Tile

*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

*To find out more about our recycled content, please visit FLOR's Environmental Efforts.