


Fall In Line - Jade

\$13.00/tile

Rows of low tight loops and slightly higher cut-pile introduce textural variation to the classic precision of pinstripes. Made in the USA 50% recycled face fibers Medium traffic Quarter-turn installation

Installation



Parquet (Quarter-Turned) Installation

General Information

Product Number	211309
Construction	Cut & Loop Pile
Soil/Stain Protection	No
Antimicrobial Treatment	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intercept
Fiber Content	Nylon
Dye Method	100% Solution Dye
Post-Industrial	48%
Post Consumer	2%
Total Recycled Content	50%
Adhesive	FLORdots™

Product Specifications

Tufted Yarn Weight	17 oz/yd ²
Machine Gauge	1/10 in
Pile Height	.17 in
Pile Thickness	.086 in
Stitches	10/in
Pile Density	7116
Total Thickness	.275 in
Size	19.7 in x 19.7 in

Performance Specifications

Indoor Air Quality	Green Label Plus Certified
Radiant Panel	(ASTM E - 648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC16-E)
Static	(AATCC - 134) < 3.0 KV
Standard Backing	GlasBac Tile
Foot Traffic	Medium

*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

*To find out more about our recycled content, please visit FLOR's Environmental Efforts.