




Mild Mannered - Salmon

\$14.00/tile

Tight, level loops of beautifully blended color offer a colorful and low maintenance design. Made in the USA 60% recycled face fibers Heavy traffic Quarter-turn installation

Installation



Parquet (Quarter-Turned) or Brick Installation

General Information

Product Number	211312
Construction	Loop Pile
Soil/Stain Protection	No
Antimicrobial Treatment	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept
Fiber Content	Nylon
Dye Method	100% Solution Dye
Post-Industrial	56%
Post Consumer	4%
Total Recycled Content	60%
Adhesive	FLORdots®;

Product Specifications

Tufted Yarn Weight	20 oz/yd ²
Machine Gauge	5/64 in
Pile Height	.14 in
Pile Thickness	.087 in
Stitches	9/in
Pile Density	8276
Total Thickness	.237 in
Size	19.7 in x 19.7 in

Performance Specifications

Indoor Air Quality	Green Label Plus Certified
Radiant Panel	(ASTM E - 648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC16-E)
Static	(AATCC - 134) < 3.0 KV
Standard Backing	GlasBac Tile
Foot Traffic	Heavy

*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

*To find out more about our recycled content, please visit FLOR's Environmental Efforts.