




# Mild Mannered - Charcoal

\$14.00/tile

A low-profile, flat weave of beautifully blended color that won't lose its cool or demand too much attention&ndash;well suited for busy spacesMade in the USA100% recycled face fibersHeavy trafficParquet (quarter-turn) installation

## Installation



Parquet (Quarter-Turned) or Brick Installation

## General Information

Product Number	211312
Construction	Loop Pile
Soil/Stain Protection	No
Antimicrobial Treatment	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept
Fiber Content	Nylon
Dye Method	100% Solution Dye
Post-Industrial	56%
Post Consumer	4%
Total Recycled Content	60%
Adhesive	FLORdots&trade;

## Product Specifications

Tufted Yarn Weight	20 oz/yd2
Machine Gauge	5/64 in
Pile Height	.14 in
Pile Thickness	.087 in
Stitches	9/in
Pile Density	8276
Total Thickness	.237 in
Size	19.7 in x 19.7 in

## Performance Specifications

Indoor Air Quality	Green Label Plus Certified
Radiant Panel	(ASTM E - 648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC16-E)
Static	(AATCC - 134) < 3.0 KV
Standard Backing	GlasBac Tile

\*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

\*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

\*To find out more about our recycled content, please visit FLOR's Environmental Efforts.