

# Full Kilt - Smoke

\$16.00/tile

The elegant look of bouclé; tweed—a multi-color, irregular pattern that's perfectly suited for the busiest of spaces  
 Made in the USA  
 100% recycled face fibers  
 Heavy traffic  
 Parquet (quarter-turn) installation

## Installation



Parquet (Quarter-Turned) Installation

## General Information

Product Number	211333
Construction	Loop Pile
Soil/Stain Protection	No
Antimicrobial Treatment	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intercept
Fiber Content	Nylon
Dye Method	100% Solution Dye
Post-Industrial	57%
Post Consumer	5%
Total Recycled Content	62%
Adhesive	FLORdots®;

## Product Specifications

Tufted Yarn Weight	26 oz/yd <sup>2</sup>
Machine Gauge	1/10 in
Pile Height	.15 in
Pile Thickness	.090 in
Stitches	7/in
Pile Density	10,400
Total Thickness	.264 in
Size	19.7 in x 19.7 in

## Performance Specifications

Indoor Air Quality	Green Label Plus Certified
Radiant Panel	(ASTM E - 648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC16-E)
Static	(AATCC - 134) < 3.0 KV
Standard Backing	GlasBac Tile

\*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

\*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

\*To find out more about our recycled content, please visit FLOR's Environmental Efforts.