


Reverb - Tan

\$8.00/tile

Closely cropped, energetic lines of vibrant color in low-profile brushed cut yarns make this one reliable performer. Made in the USA 100% recycled face fibers Medium traffic Parquet (quarter-turn) installation

Installation



Parquet (Quarter-Turned) Installation

General Information

Product Number	211338
Construction	Cut Pile
Soil/Stain Protection	No
Antimicrobial Treatment	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intercept
Fiber Content	Nylon
Dye Method	100% Solution Dye
Post-Industrial	56%
Post Consumer	4%
Total Recycled Content	60%
Adhesive	FLORdots™

Product Specifications

Tufted Yarn Weight	18 oz/yd ²
Machine Gauge	1/10 in
Pile Height	.13 in
Pile Thickness	.077 in
Stitches	12/in
Pile Density	8416
Total Thickness	.234 in
Size	19.7 in x 19.7 in

Performance Specifications

Indoor Air Quality	Green Label Plus Certified
Radiant Panel	(ASTM E - 648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC16-E)
Static	(AATCC - 134) < 3.0 KV
Standard Backing	GlasBac Tile
Foot Traffic	Medium

*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

*To find out more about our recycled content, please visit FLOR's Environmental Efforts.