



Milliner - Grey

\$14.00/tile

A tight, dense weave of tonal striations accentuated with irregular, pinstripe pops of color. Coordinates nicely with Level Setting for a stylish combo. Made in the USA 100% recycled face fibers Heavy traffic Parquet (quarter-turn) installation

Installation



Parquet (Quarter-Turned) Installation

General Information

Product Number	211343
Construction	Loop Pile
Soil/Stain Protection	No
Antimicrobial Treatment	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept
Fiber Content	Nylon
Dye Method	100% Solution Dye
Post-Industrial	55%
Post Consumer	3%
Total Recycled Content	58%
Adhesive	FLORdots™

Product Specifications

Tufted Yarn Weight	15 oz/yd ²
Machine Gauge	5/64 in
Pile Height	.070 in
Pile Thickness	.024 in
Stitches	8.66/in
Pile Density	22,500
Total Thickness	.203 in
Size	19.7 in x 19.7 in

Performance Specifications

Indoor Air Quality	Green Label Plus Certified
Radiant Panel	(ASTM E - 648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC16-E)
Static	(AATCC - 134) < 3.0 KV
Standard Backing	GlasBac Tile

*(PI) Post-Industrial--percentage of recycled content derived from industry scraps.

*(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.

*To find out more about our recycled content, please visit FLOR's Environmental Efforts.