

## Down To Earth

### General Information


Product Number	21-1402
Construction	Loop Pile
Soil Stain Protection	No
Antimicrobial Treatment	Yes
Fiber Content	Nylon
Dye Method	100% Solution Dye
Post-Industrial	66%
Post Consumer	12%
Total Recycled Content	78%
Adhesive	FLORdots
Installation	Parquet (Quarter-Turned), Non-Directional

### Product Specification


Tufted Yarn Weight	28 oz/yd <sup>2</sup>
Machine Gauge	1/10 in
Pile Height	.20 in
Pile Thickness	.141 in
Stitches	7.3/in
Pile Density	7149
Total Thickness	.337 in
Tile Size	19.7 in x 19.7 in

### Performance Specification


Indoor Air Quality	GREEN LABEL PLUS CERTIFIED
Radiant Panel	(ASTM E - 648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC16-E)
Static	(AATCC - 134) < 3.0 KV
Standard Backing	GlasBac Tile



Monolithic  
(Straight)



Non-Directional



Parquet  
(Quarter-Turned)

Post-Industrial: percentage of recycled content derived from industry scraps

Post Consumer: percentage of recycled content derived from materials recycled by consumers and businesses

Getting Greener Every Day. Learn more at [FLOR.com/responsible](https://www.flor.com/responsible)