


Reverb - Smolder

\$8.00/tile

Closely cropped, energetic lines of vibrant color in low-profile brushed cut yarns make this one reliable performer. Made in the USA100% recycled face fibers Medium traffic Parquet (quarter-turn) installation

Installation



Parquet (Quarter-Turned) Installation

General Information

211338	•
Cut Pile	•
No	•
(AATCC 138 Washed) (AATCC 174 F	arts 2&3) Intersept
Nylon	
100% Solution Dye	
56%	
4%	
60%	
FLORdots™	
	Cut Pile No (AATCC 138 Washed) (AATCC 174 F Nylon 100% Solution Dye 56% 4% 60%

Product Specifications

Tufted Yarn Weight	18 oz/yd2	
Machine Guage	1/10 in	
Pile Height	.13 in	
Pile Thickness	.077 in	
Stitches	12/in	
Pile Density	8416	
Total Thickness	.234 in	
Size	19.7 in x 19.7 in	

Performance Specifications

Indoor Air Quality	Green Label Plus Certified
Radiant Panel	(ASTM E - 648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC16-E)
Static	(AATCC - 134) < 3.0 KV
Standard Backing	GlasBac Tile

- *(PI) Post-Industrial--percentage of recycled content derived from industry scraps.
- *(PC) Post Consumer--percentage of recycled content derived from materials recycled by consumers and businesses.
- *To find out more about our recycled content, please visit FLOR's Environmental Efforts.